







Technical data

Multiphase supply voltage	380 - 415 V 2N/3N
Single-phase supply voltage	220 - 240 V
Frequency	50 - 60 Hz
Maximum power consumption	7600 W (4400 W / 3600 W)
Three-phase power supply/fuse protection	3 x 16 A (standard connection)
Two-phase power supply/fuse protection	2 x 16 A
Single-phase power supply/fuse protection	1 x 32 A (1 x 20 A / 1 x 16 A)
Dimensions (width x depth x height)	830 x 515 x 199 mm
Weight (incl. accessories/packaging)	23,0 kg
Surface material	Glass ceramic
Cooktop extractor power levels	1 - 9, P
Cooktop power levels	1 - 9, P
duct connection	BORA Ecotube
Size of front cooking zone	230 x 230 mm
Size of rear cooking zone	230 x 230 mm
Front cooking zone output	2100 W
Rear cooking zone output	2100 W
Front cooking zone power setting output	3000 W
Rear cooking zone power setting output	3000 W

Product description

- Intuitive sControl control
- Minimum volume
- Simple cleaning
- Oversized surface induction cooking zones
- Minimalistic design
- Variable heat retention function
- Maximum storage space
- Compact size
- Integrated grease drip pan
- automatic bridging function

Scope of delivery

- Surface induction glass ceramic cooktop with integrated cooktop extractor - exhaust air PUXA
- air inlet nozzle
- stainless steel grease filter
- operating and installation instructions
- Mounting clamps
- sealing tape
- height adjustment plate set
- Housing cover power supply
- Installation accessories for the power supply

Accessories

- Stainless steel grease filter PUEF
- Air inlet nozzle PUXED
- UDB25 sealing tape
- BKR830 cooktop frame
- Air purification box PULB
- Air purification box telescopic pull-out PULBTA
- Surface induction grill pan KWGPFI

Product- and planning instructions

- The power supply cable must be provided at the installation site
- Front power socket
- The BORA Ecotube duct system is optimally tailored to the BORA cooktop extractors and guarantees 100% functionality and optimum performance
- Ensure sufficient ventilation of the area below the cooktop.
- Installation type: flush or surface-mounted
- The drawers and/or shelves in the floor unit must be removable for maintenance and cleaning purposes
- Please note that induction-compatible cookware must be used on induction cooktops
- The X PURE cooktop extractor system can be combined with all BORA sockets
- Not compatible with BORA universal extractors